

ARCS PROCEDURE:	CHECKING RED AND YELLOW FLAGS ON THE WSI	PRO(WSI)-014.000
Author: T. Tooman		May 4, 1999 Page 1 of 2

Checking Red and Yellow Flags on the WSI

I. Purpose:

To check the red and yellow flags on the WSI when a message appears on the WSI monitor.

II. Cautions and Hazards:

None.

III. Requirements:

None.

IV. Procedure:

A. Steps:

1. Press the 's' key.
2. You will see details about any red flags. There may or may not be any information in this area. If you saw a red flag message on the display, there will be information about red flag in this location. When you have a red flag please note the information in this area into the SDL report.
3. Press ENTER.
4. You will see details about any yellow flags. There may or may not be any information in this area. If you saw a yellow flag message on the display, there will be information about yellow flag in this location. When you have a yellow flag please note the information in this area into the SDL report.
5. Press 'n' key to return to the regular display (i.e. the picture).
 - **NOTE:** When you see a yellow flag that talks about the GPS, please look at the GPS on side of the WSI blue box. IF there is not a display on the GPS, press the red button for 2-3 seconds. When you turn the GPS on, a display will be visible. The first screen of the GPS is a world turning.

V. References:

None.

ARCS PROCEDURE:	CHECKING RED AND YELLOW FLAGS ON THE WSI	PRO(WSI)-014.000
Author: T. Tooman		May 4, 1999 Page 2 of 2

VI. Attachments:

None.